



GREE ELECTRIC APPLIANCES, INC. OF ZHUHAI

Add: West Jinji Rd, Qianshan, Zhuhai, Guangdong, China 519070
Tel: (+86-756) 852 2218 Fax: (+86-756) 866 9426
Email: gree@gree.com.cn Http://www.gree.com

HONG KONG GREE ELECTRIC APPLIANCES SALES LIMITED

Add: Unit 2612, 26/F., Miramar Tower 132 Nathan Road, TST, Kowloon, HK
Tel: (852) 3165 8898 Fax: (852) 3165 1029

Note:
Gree is committed to continuously improving its products to ensure the highest quality and reliability standards, and to meet local regulations and market requirements.

All features and specifications are subject to change without prior notice.

All images provided in this catalogue are used for illustration purposes only.
Copyright© Gree Electric Appliances, Inc. of Zhuhai. All rights reserved.

GC-1409-01




Distributor information

GREE Multi VRF 5



Gree GMV- History of Development





GMV5 DC Inverter Multi VRF System with its high-efficient inverter compressors have four exciting features which are different from those found on traditional inverter air conditioners: excellent energy-saving effect, more reliable and precise operation, smarter network control, providing users with best air conditioning experience.

CONTENTS

05 GMV5

25 GMV5 Mini & Slim

33 GMV5 Heat Recovery

44 Indoor Units

65 Control System

83 Energy Recovery Ventilation(ERV)



GMV5




Key Features

All DC Inverter Technology to Improve Compression Efficiency


All DC inverter compressor and high-performance high pressure chamber are adopted to reduce loss of overheat and improve compression efficiency from direct intake. Compared with low pressure chamber, the compression efficiency is improved. High-efficient permasyon motor is adopted to provide better performance than traditional DC inverter compressor.

All DC Inverter Compressor

- All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.




- High-efficient permasyon motor is adopted to provide better performance than traditional DC inverter compressor.




- Technology of maximum torque control with minimum current**

It can reduce energy loss caused by device winding so as to realize higher efficiency.




- Low-frequency torque control**

It can directly control motor torque, through which fan motor can run at a low speed. Users will feel more comfortable while requirements of the system are also met.




- 180° Sine Wave DC Speed Varying Technology**
It can satisfy various places' demands for different temperature and is able to save a great deal of electricity and provide users with utmost comfort at the same time.




Sensorless DC Inverter Fan Motor

- Stepless speed regulation ranges from **5Hz** to **65Hz**. Compared with traditional inverter motors, the operation is more energy-saving.



- Sensorless control technology guarantees lower noise, less vibration and steadier operation.



88HP Max Capacity-The Largest Free Combination

Max capacity of single outdoor unit reaches **22HP** and max combination capacity is even up to **88HP**, in an industry leading level.

Max combination capacity is extended to 88HP



Money is saved in system cost and piping



Compact design

With compact design, the outdoor unit can be carried to the roof of building through elevator, with no need of crane. It is easier for delivery and installation.



Non-polar CAN Technology to Improve Communication Efficiency

- Gree is the first one to adopt non-polar CAN communication technology in the industry. CAN communication technology provides quicker system response speed, more convenient installation debugging and more reliable communication data.


Performance Index	Company A Multi-VRF Network	GMV5 DC Inverter CAN Network
Reliability	Software check	Hardware check, more reliable
	One unit's communication error may lead to a breakdown of the whole network	If one unit has errors, it will exit from the network without any influence to other units.
Communication Efficiency	Low utilization	High utilization
	Communication speed is about 10Kbps.	Communication speed is 20Kbps.
Compatibility	One main network, difficult to add new equipment	Multiple main networks, easy to add new equipment.
Communication Distance	1000m	1500m

- The non-polar CAN communication technology is applied to support flexible wiring installation, greatly reducing construction difficulties.



Wide Range of Voltage and Operation Condition

Working voltage range of GMV5 system has been improved to **320V~460V**, which surpasses the national standard of 342V~420V. For places with unsteady voltage, this system can still be running well.



Outdoor operation temperature range is improved to **-5°C~52°C in cooling** and **-20°C~24°C in heating**.




Wider Applicable Location

GMV5 can realize a combination of 4 outdoor unit modules connecting with as many as **80** indoor units. It's especially applicable for business building or hotels.




Refrigerant Storage and Distribution

The GMV5 system is designed without liquid receiver and the excess refrigerant is stored in the piping, which can minimize the refrigerant charging volume and enhance the control accuracy of refrigerant.



High Efficiency and More Energy Saving

Thanks to the advanced all DC inverter technology, optimized system design and accurate intelligent control technology, IPLV of GMV5 All DC Inverter Multi VRF System is up to 6.8.



New Generation of Energy-saving Operation Control Technology with Energy Saving Up to 20%


The GMV5 system has 2 modes for energy saving, which can be chosen to meet different electricity demands.

Mode 1:

In auto energy-saving mode, the system will self-adjust parameters according to the operation status, thus to lower the cost of electricity. Up to 15% of energy can be saved.


Mode 2:

In compulsory energy-saving mode, the system will limit power output forcibly. Up to 20% of energy can be saved.



Comfortable Heating

Advanced intelligent defrosting mode is adopted. Gree advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.




Accurate Intelligent Allocation Technology of Capacity and Output of Optimal Portion to Ensure Highest Efficiency

- When total load demands more than 75% of a running system's capacity, one more unit will automatically start;
- When total load demands less than 40% of a running system's capacity, one unit will automatically shut down;
- Therefore, each unit shares 40%-75% of the total load.
- Experiments show that an air conditioner costs the least energy when it's operating within 40%-75% of its capacity.

	 Company A	 Gree GMV
Allocation Method	10HP(full load) + 2HP(low load)	6HP(partial load) + 6HP(partial load)
Performance Compared	Unit costs more energy and may be soon damaged.	Unit costs less energy and can always be kept in good condition.



Output of Optimal Portion to Ensure Highest Efficiency

The best heating or cooling performance can be realized in the most energy-saving way. DC inverter compressor and DC inverter fan will also be operating in this way to ensure high efficiency.



Sub-cooling Control Technology to Ensure Optimal Cooling and Heating

- Heat exchange loop can control the first subcooling process of heat exchanger. Subcooling degree can reach 11 C.
- Subcooling loop can realize 9 C second subcooling to guarantee cooling and heating performance.



Temperature Controlled by Wired Controller with Higher Efficiency and More Energy Saving

Through setting temperature lower limit in cooling or dry mode, and setting temperature upper limit in heating, 3D heating or heat supply mode, the system is able to operate in a smaller temperature range so as to achieve energy saving.


Comfortable Design for A Better Life

The GMV5 system has a wide range of working conditions. Whether it's in a cool winter or a hot summer, normal operation is guaranteed with the least noise, making users feel more comfortable.

Outdoor Unit Quiet Mode and Quiet Control

Quite at night

The system can remember the highest outdoor temperature. When night comes, the system will automatically turn to quiet mode. There are 9 quiet modes which can be set according to actual needs.




Quite in compulsion

The system can also be set in this mode to ensure low noise as long as it is operating. Noise is as low as 45dB(A).



Quiet Control

1. Optimized Bossing Design
After many times of CFD tests, a new fan bossing structure has been developed to reduce vibration of fan during running. Noise can be reduced by 3dB(A).




2. Aerodynamics 3D Axial Fan
Compared with conventional fan, it can increase air volume by 12%, improving efficiency as well as lowering noise.




Indoor Unit Quiet

The indoor unit of the GMV5 system also adopts DC inverter motors to realize stepless regulation. According to indoor temperature or people's actual needs, users can set this mode through wired controller. Noise is as low as 25dB(A).




Fast Start-up in Heating

DC Compressor is first started to avoid too much electric current. Inverter compressor can operate in high frequency once starts up, so as to produce more heat.



7 Levels of Indoor Fan Speed for Option

Indoor fan speed can be set in 7 levels by wired controller. They are auto, low speed, medium-low speed, medium speed, medium-high speed, high speed and turbo. When the wired controller is on, press "FAN" button to set indoor fan speed circularly as below:




Excellent Performance Ensured by Advanced Technology

Through 10 years' of research and development, Gree GMV5 has been further upgraded to a high level from electrical components, mechanical parts, control technology to communication technology.

Two-stage Oil Separation Control Technology (Patented)



First-stage oil separator adopts a filtration expansion valve with separation efficiency of 98%; Second-stage oil separator will separate the remained 2% refrigerant oil with separation efficiency of 95%. General oil separation efficiency reaches 99.9%.



Oil Return Control Technology


New Oil Return Control

Gree new oil return control technology effectively controls system oil return and oil storage status of each compressor, which greatly improves the operation lifespan of compressor.



Specialized Compressor Oil Storage Control


The system applies specialized compressor oil storage technology, which can control the lowest oil level for compressor operation.



Oil Balance Control Technology


Oil Balance between Each Module

Based on the actual status of each module and compressor, the system can regulate compressor's operation and realize oil balance of each module.



Oil Balance between Each Compressor


Refrigerant is taken into the compressor by the suction pipe and then runs through the cooling system. It can control the oil level and minimum oil volume required by each compressor so as to realize oil balance between each compressor.



Intelligent Detection Control

Pressure Sensor Detection Control

Pressure sensor can precisely detect system high pressure and low pressure, and adjust output of fan and compressor, so as to make sure the system can work under the most energy-saving pressure condition.




Temperature Sensor Detection Control

Various temperature sensors are equipped to detect ambient temperature, indoor temperature and refrigerant's evaporating temperature, from which the operation status can be measured.


Multi Electronic Expansion Valves Control

Outdoor electronic expansion valve not only has throttling effect, but also control refrigerant flow. The system adopts multi electronic expansion valves control with 960 grades regulated by two electronic expansion valves, so as to regulate refrigerant flow precisely and ensures reliable operation of system.



Smaller Impact to Power Grid


The start-up frequency of inverter compressor is gradually increased from 0Hz to the appointed operation frequency. The start-up current of compressor rotor is decreased by reducing load torque, hence impact to power grid during start-up is reduced and electromagnetic impact to compressor is reduced too.



Modules Rotation Operating to Maximize Lifespan

Modules 8h rotation operating


The operating priority sequence of the outdoor unit modules will be changed without restart when the system accumulatively operates for 8 hours, which can maximize the service life of the system.



Highly Anticorrosive Golden Fins


The primary material of Golden Fin is Al-Mn (Aluminum-Manganese) anti-rust alloy, which is coated with the Golden Protection Layer (Components: Epoxy Resin & Modified Acrylic, Silicon free), the anti-corrosion performance in salt-spray testing is 200%~300% higher than normal Blue Fin*.

Note: Salt-spray testing result is from GREE materials chemistry testing laboratory.




Emergency Auto-Off Control

The outdoor unit can be linked with a fire alarm signal. In case of emergency, unit can automatically turn off to avoid risk or further loss.



Electricity Shortage Identification

The outdoor unit can receive a power signal of electricity shortage. In some places like first-class hotels, if diesel generator is used temporarily for providing electricity, outdoor unit will send the electricity shortage signal to indoor unit. In this case, only VIP rooms can be provided with air conditioning service.



Excellent Emergency Operation Function to Ensure Reliable Operation

Emergency Function

The GMV 5 system can realize a combination of 4 outdoor unit modules. When error is occurred to one of the modules, the others will perform the emergency operation to sustain the air conditioning.



Emergency Operation of Compressor

All the compressors in each single module are DC Inverter based, when one compressor has error, others will perform the emergency operation.



Emergency Operation of Fan


Double-fan design fan ensures that one fan can still work even if the other one has error.



Easy Installation for Various Kinds of Construction

ODU High Static Pressure Design

System has 4 levels of static pressure that can be set. Up to 82Pa pressure can be set for an outdoor unit. This design is especially useful when an outdoor unit needs to be placed indoors.




1000m Pipe Design for Flexible Installation

GMV5 system can be applied in different types of building construction. One of its advantages is the simple pipe design, which will make installation much simpler and reduce installation cost.

- Max total pipe length reaches 1000m (with limitation)
- Actual pipe length between the outdoor unit and the farthest indoor unit: 165m
- Max height difference between indoor unit and outdoor unit: 90m


Note:
a: Distance between the first branch and the farthest indoor unit.
b: Distance between the first branch and the nearest indoor unit.
a-b≤40m



Intelligent Debugging for Convenient Construction


GMV5 has five auto debugging features:

- Automatic allocation of IDU and ODU addresses
- Automatic detection of IDU and ODU quantity
- Automatic detection of errors
- Automatic start-up of debugging
- Real-time judgment of pipe errors



Auto Refrigerant Recovery for Convenient Operation

When auto refrigerant recovery function is set and cut-off valve of liquid pipe is closed during maintenance, the system will automatically operate compressor, EXV, solenoid valve and fan, etc. Taking advantage of compressor power, the refrigerant is recovered at the condensing side of outdoor unit to achieve environmental effect. Meanwhile, system low pressure is displayed simultaneously during refrigerant recovery.




Inspection Window for Convenient Checking

Inspection window is available for quick checking of system operation status. No need to open panel for checking, which will be more time-saving and easier for maintenance.




Flexible Wiring

Common wire can meet the communication demand with no need of specialized communication wire. Common sheath twisted pair cable can be used as there is no polarity requirement.



Auto Addressing of Outdoor and Indoor Unit

CAN network is adopted to achieve auto addressing of outdoor and indoor unit. It can allocate IDU and ODU addresses and detect IDU and ODU quantity, which greatly improves construction efficiency.




Professional Hotel Functions

Gree GMV5 provides hotels with unique season setting function and key-card control function.

Season Setting

Cooling or heating mode can be deactivated during a certain season to avoid affecting unit's normal operation due to mode conflict.



Key-card Control for Hotel Management

The unit can be turned on or off by inserting or removing the key-card. When the key-card is removed, the system can remember all the setting and stop operation. When the key-card is inserted back, the system will be under standby mode or operate according to the status before removing key-card. It is well suited to hotels, restaurants, etc.



GMV5 Mini & Slim




Key Features

All DC Inverter Technology to Improve Compression Efficiency


All DC inverter compressor and high-performance high pressure chamber are adopted to reduce loss of overheat and improve compression efficiency from direct intake. Compared with low pressure chamber, the compression efficiency is improved. High-efficient permasyon motor is adopted to provide better performance than traditional DC inverter compressor.

All DC Inverter Compressor


- All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.




- High-efficient permasyon motor is adopted to provide better performance than traditional DC inverter compressor.





- Technology of maximum torque control with minimum current**
It can reduce energy loss caused by device winding so as to realize higher efficiency.



- 180° Sine Wave DC Speed Varying Technology**
It can satisfy various places' demands for different temperature and is able to save a great deal of electricity and provide users with utmost comfort at the same time.




- Low-frequency torque control**
It can directly control motor torque, through which fan motor can run at a low speed. Users will feel more comfortable while requirements of the system are also met.




Sensorless DC Inverter Fan Motor

- Stepless speed regulation ranges from **5Hz** to **65Hz**. Compared with traditional inverter motors, the operation is more energy-saving.




- Sensorless control technology guarantees lower noise, less vibration and steadier operation.



Sensorless DC Inverter Fan Motor


The indoor unit adopts high-efficiency brushless DC motor. Compared with conventional motor, the efficiency of brushless DC motor is improved by more than **30%**. Meanwhile, the design of evaporation capacity flow is optimized through emulation software of refrigeration system and the heat exchange amount of evaporator is greatly improved.



High-efficiency Digital PFC Control *

High-efficiency PFC control technology is adopted with efficiency improved by about 1% compared with conventional PFC. For the air conditioner with rated power of 5kW, **50W** of electricity can be saved every hour and **1.2kW** of electricity can be saved every day.

*This feature is applicable for GMV5 Mini only.



Wider Operation Condition Range

The unit adopts DC motor with more accurate high pressure control, which effectively solves the high pressure control problem in low ambient temperature cooling. So the operation range in cooling is wider.

Company A	Gree GMV5 Mini	Gree GMV5 Slim
Cooling: -10~48°C Heating: -20~27°C	Cooling: -5~48°C Heating: -20~27°C	Cooling: -5~50°C Heating: -20~27°C

Comfortable and Quiet Mode


Low Noise of Outdoor Unit

- The advanced sub-cooling control technology is applied to reduce the liquid flow noise of indoor unit in cooling operation.
- Non-commutative oil return technology in heating and optimization control logic are adopted to reduce the liquid flow noise of indoor unit in oil return course of heating operation.



Low Noise of Indoor Unit

- The pioneering and patented high-efficiency centrifugal fan blade and low-noise volute are adopted. Meanwhile, the imported silent valve is adopted to reduce noise of entire unit as low as 22db(A).
- By adopting the optimal inlet angle of centrifugal fan blade and optimal diameter ratio between internal and external circles of impeller, the air volume is increased and fan noise is decreased greatly.




Intelligent Temperature Control Technology

Intelligent temperature control technology is adopted for super fast cooling or heating, so that indoor temperature will reach set temperature more quickly.




Comfortable Heating

Advanced intelligent defrosting mode is adopted. Gree advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.



Non-commutative Oil Return Technology in Heating



The unit can achieve non-commutative oil return in heating when outdoor ambient temperature is within 0~20°C. Thanks to this technology, indoor ambient temperature is more stable and comfort is improved in heating mode.



Reliable Operation

Compressor Closed-loop Startup Technology with More Reliable Startup

The self-innovative closed-loop startup control technology is adopted. Thanks to this technology, the startup current is small and startup is more reliable.




High Anti-interference Ability

The latest CAN bus communication technology is adopted, with non-polar communication and high anti-interference ability. Common communication wire can meet the communication demand with no need of specialized shielded wire. The customers can buy the communication wire by themselves, greatly reducing installation difficulties.



Advanced High-frequency Transformer with More Stable Voltage

- The advanced switching power supply is adopted with lower power consumption and higher power efficiency.
- Wide voltage-regulation range ensures stable voltage output when the voltage of grid fluctuates.
- Compared with conventional transformer, the size of high-frequency transformer is small and the weight is light.



Ultra-long Connection Pipe for More Convenient Connection

Under the subcooling control technology gained by adding subcooler, the indoor unit and outdoor unit of GMV5 mini can operate reliably with longer connection pipe.

	Company A	Gree GMV5 Mini & Slim
Max total length of connection pipe	150m	300m
Connection pipe length of the farthest indoor unit	70m	120m

Adopting Advanced Refrigerant Cooling Technology

Drive IPM adopts refrigerant for cooling, which eliminated the limitation and instability of heat radiation of aluminum fins by fan cooling. Moreover, the controller can operate more reliable and service life is longer.

*This feature is applicable for GMV5 Slim only.



GMV5 Mini & Slim Line Up

Mini Line up

HP	Model	Product Outlook
4	GMV-120WL/A-T	
5	GMV-140WL/A-T	
6	GMV-160WL/A-T	

Slim Line up

HP	Model	Product Outlook
7	GMV-H200WL/A-X	
8	GMV-H224WL/A-X	
9	GMV-H250WL/A-X	
10	GMV-H280WL/A-X	
11	GMV-H308WL/A-X	
12	GMV-H335WL/A-X	

Mini

50/60 Hz

Model			GMV-120WL/A-T ¹	GMV-140WL/A-T ¹	GMV-160WL/A-T ¹
Capacity range	HP		4	5	6
Capacity	Cooling	kW	12.1	14	16
	Heating	kW	14	16.5	18.5
EER		kW/kW	3.97	3.52	3.3
COP		kW/kW	4.28	4.14	3.96
IPLV	Cooling	kW/kW	/	/	/
Power supply		V/Ph/Hz	220-240V-1Ph-50Hz&208-230V-1Ph-60Hz		
Max. Circuit/Fuse Current		A	28.1/32	31.8/32	33.8/40
Power consumption	Cooling	kW	3.05	3.98	4.85
	Heating	kW	3.27	3.99	4.67
Maximum drive IDU NO.		unit	7	8	9
Refrigerant Charge volume		kg	5	5	5
Sound pressure level		dB(A)	55	58	58
Connecting pipe	Liquid	mm	Φ9.52		
	Gas	mm	Φ15.87		
Dimension (W*D*H)	Outline	mm	900*340*1345		
	Package	mm	998*458*1515		
Net weight/Gross weight		kg	110/120	110/120	110/120
Loading quantity	40' GP	set	57	57	57
	40' HQ	set	57	57	57

*1 | This series outdoor unit cannot match with US air handler, fresh air processing unit and high static ESP duct type unit.

Slim

50/60 Hz

Model			GMV-H200WL/A-X ¹	GMV-H224WL/A-X ¹	GMV-H250WL/A-X ¹	GMV-H280WL/A-X ¹	GMV-H308WL/A-X ²	GMV-H335WL/A-X ¹
Capacity range	HP		7	8	9	10	11	12
Capacity	Cooling	kW	20.0	22.4	25.0	28.0	30.8	33.5
	Heating	kW	22.4	25.0	27.0	31.5	33.9	37.5
EER		kW/kW	/	/	/	/	/	/
COP		kW/kW	/	/	/	/	/	/
IPLV	Cooling	kW/kW	6.1	6.1	6.0	6.0	6.0	6.0
Power supply		V/Ph/Hz	380-415-3Ph-50/60Hz					
Max. Circuit/Fuse Current		A	25	25	25	25	25	25
Power consumption	Cooling	kW	6.5	7.2	7.7	9.4	10.3	11.0
	Heating	kW	5.6	6.1	7.2	8.6	9.6	10.4
Maximum drive IDU NO.		unit	12	13	15	17	18	20
Refrigerant Charge volume		kg	5.0	5.5	6.0	7.5	8.0	8.8
Sound pressure level	Cooling	dB(A)	57	58	59	59	59	60
	Heating	dB(A)	58	59	60	60	60	61
Connecting pipe	Liquid	mm	Φ9.52	Φ9.52	Φ9.52	Φ12.7	Φ12.7	Φ12.7
	Gas	mm	Φ19.05	Φ19.05	Φ19.05	Φ25.4	Φ25.4	Φ25.4
Dimension (W*D*H)	Outline	mm	940*320*1430	940*320*1430	940*320*1430	940*460*1615	940*460*1615	940*460*1615
	Package	mm	1033*433*1580	1033*433*1580	1033*433*1580	1033*573*1765	1033*573*1765	1033*573*1765
Net weight/Gross weight		kg	133/144	133/144	133/144	160/175	165/180	170/185
Loading quantity	40' GP	set	54	54	54	44	44	44
	40' HQ	set	54	54	54	44	44	44

Note-

1) Testing conditions of rated cooling capacity: indoor 27°CDB/19°CWB, outdoor 35°CDB, connection pipe length of 5m, no height difference between units.

2) Testing conditions of rated heating capacity: indoor 20°CDB, outdoor 7°CDB/6°CWB, connection pipe length of 5m, no height difference between units.

3) The total indoor unit capacity shall be within 50% to 130% of outdoor unit capacity. Correction of other parameters can be referred to the unit capacity correction sheet.

4) The above-mentioned parameters are tested with standard connection pipe length. In actual engineering, please arrange correction according to the capacity correction with long connection pipe.

*1 - This product is under development. The parameters are estimated, please refer to the value on the nameplate.


GMV5 Heat Recovery




Key Features

High Efficiency


GMV5 Heat Recovery System embodies the excellent features of GMV5 (DC inverter technology, DC fan linkage control, precise control of capacity output, balancing control of refrigerant, original oil balancing technology with high pressure chamber, high-efficiency output control, low-temperature operation control technology, super heating technology, high adaptability for project, environmental refrigerant). Its energy efficiency is improved by 78% compared with conventional multi VRF.



ECOP of heat recovery system
 $\xi = (13.0 + 17.0) / 4.5 = 6.67$



EER of common system
 $\xi_1 = 13.0 / 3.0 = 3.25$



COP of common system
 $\xi_2 = 17.0 / 5.0 = 3.4$

When the cooling capacity and heating capacity of common system are equivalent to the capacity of heat recovery system, its energy efficiency ratio is:


$\xi_2 = (13.0 + 17.0) / (3.0 + 5.0) = 30.0 / 8.0 = 3.75$

The energy efficiency ratio of heat recovery system is higher than common system:

$(6.67 - 3.75) \times 100\% / 3.75 = 78\%$


Note: Working conditions of above-mentioned test: outdoor temperature 7°C/6°C, indoor temperature in cooling 27°C/19°C, indoor temperature in heating 20°C/15°C.

Five Efficient Operation Modes




All DC Inverter Technology to Improve Compression Efficiency

- All DC inverter compressor is used in this system. It can directly intake gas to reduce loss of overheat and improve efficiency.



- High-efficient permasyn motor is adopted to provide better performance than traditional DC inverter compressor.




High Pressure Chamber Design

What's high pressure chamber?

The low-temperature and low-pressure refrigerant gas inhaled from the suction inlet of compressor will change to high-temperature and high-pressure gas after compression by scroll plate. Then the gas will go out from the exhaust at the center of fixed scroll and get into the lower chamber of compressor, so that the chamber of compressor is in high temperature and high pressure.


What's the benefits of high pressure chamber?

High pressure chamber compressor inhales directly to reduce overheat suction loss and improve compression efficiency.



HP chamber structure can raise the high and middle frequency performance


New DC motor (concentrated winding) raises the low frequency performance




Sensorless DC Inverter Fan Motor

Stepless speed regulation ranges from **5Hz** to **65Hz**. Compared with traditional inverter motors, the operation is more energy-saving.

Sensorless control technology guarantees lower noise, less vibration and steadier operation.



Before



After


Wide Range of Voltage to Ensure a Steady System Running

Working voltage range of GMV5 system has been improved to **320V-460V**, which surpasses the national standard of 342V-420V. For places with unsteady voltage, this system can still be running well.



Unique PCB Protection

With unique high efficiency radiating air-dust design, the outdoor electric box is designed as water-proof, dust-proof, damp-proof and well-ventilated, which can ensure the required conditions for the electric elements even if in tropical conditions, highly improved the system reliability and service life.



Wider Applicable Location

GMV5 can realize a combination of 4 outdoor unit modules connecting with as many as **80** indoor units. It's especially applicable for business building or hotels.




Max. IDU Connection: **80** sets

Comfortable Design for A Better Life


Intelligent Quiet Function at Night

- Quiet at night**
Intelligently adjustment of outdoor fan control can minimize the during night time. Up to 8dB(A) can be reduced and operation noise at night is as low as 50dB(A).




Low noise design

HP Chamber compressor has lower exhaust pressure fluctuation so that noise is lower.



The optimized design of condensing fan blade reduces the air flow turbulence among blades, so that the noise is lower.



Individual Control for More Energy Saving


The set temperature of each room may vary by the individual thermostat control of each indoor unit. The cooling and heating operation can be performed at the same time.



Wide Operation Range



The unit can operates in wide range, greatly reducing the ambient temperature limitation.

Note:
If the required capacity of indoor units is 50% higher than outdoor unit, cooling range may be lower to -15°C.
If the required capacity of indoor units is 50% higher than outdoor unit, cooling range may be up to -5°C



Comfortable Heating

Advanced intelligent defrosting mode is adopted. Gree advanced intelligent defrosting mode will choose the best defrosting way according to outdoor temperature and operation status to realize intelligent defrosting, effectively improving heating effect and performance. While in traditional defrosting mode, timing defrosting is adopted, which not only affects comfort but also reduces energy efficiency.



Excellent Performance Ensured by Advanced Technology

Modules Rotation Operating to Maximize Lifespan

Modules 8h rotation operating

The operating priority sequence of the outdoor unit modules will be changed without restart when the system accumulatively operates for 8 hours, which can maximize the service life of the system.



Excellent Emergency Operation Function to Ensure Reliable Operation

Emergency Function

The GMV 5 system can realize a combination of 4 outdoor unit modules. When error is occurred to one of the modules, the others will perform the emergency operation to sustain the air conditioning.



Emergency Operation of Compressor

All the compressors in each single module are DC Inverter based, when one compressor has error, others will perform the emergency operation.




Emergency Operation of Fan

Double-fan design fan ensures that one fan can still work even if the other one has error.



Highly Anticorrosive Golden Fins



The primary material of Golden Fin is Al-Mn(Alumium-Manganese) anti-rust alloy, which is coated with the Golden Protection Layer(Components: Exoxy Resin & Modified Acrylic, Sillon free), the anti-corrosive performance in salt-spray testing is 200%~300% higher than normal Blue Fin*.



Oil Return Control Technology


New Oil Return Control

Gree new oil return control technology effectively controls system oil return and oil storage status of each compressor, which greatly improves the operation lifespan of compressor.



Specialized Compressor Oil Storage Control

The system applies specialized compressor oil storage technology, which can control the lowest oil level for compressor operation.



Easy Installation and Maintenance

Compact Design

With compact design, the outdoor unit can be carried to the roof of building through elevator, with no need of crane. It is easier for delivery and installation.



Easy Transportation

Optimized base frame
Optimized base frame, the locating and fixing of the outdoor unit during installation is more convenient and reliable.



Transportable by forklift




Five-way piping connection
Piping and wiring are available to the front and back, left and right, and bottom.

The five-way piping connection reduces installation difficulty and cost, improves the installation efficiency.



Easy Maintenance

Inspection window is available for quick checking of system operation status. No need to open panel for checking, which will be more time-saving and easier for maintenance.






Error Display & Self-diagnostic Function
Through LED display (different combinations of ON, OFF, or BLINK) on the main board, the malfunction can be judged.



GMV5 HR Line Up

HR Line up

HP	Model	Product Outlook
8HP	GMV-Q224WM/B-X	
10HP	GMV-Q280WM/B-X	
12HP	GMV-Q335WM/B-X	
14HP	GMV-Q400WM/B-X	
16HP	GMV-Q450WM/B-X	

Model	Product Outlook
NCHS1B	
NCHS4B	
NCHS8B	

Specifications and Parameters

50/60 Hz

Model		GMV-Q224WM/B-X	GMV-Q280WM/B-X	GMV-Q335WM/B-X	GMV-Q400WM/B-X	GMV-Q450WM/B-X	
Capacity range	HP	8	10	12	14	16	
Capacity	Cooling	kW	22.4	28	33.5	40	45
	Heating	kW	25	31.5	37.5	45	50
EER		kW/kW	4.07	3.73	3.76	3.54	3.33
COP		kW/kW	4.17	3.89	3.68	3.85	3.62
IPLV	Cooling	kW/kW	/	/	/	/	/
Power Supply	V/Ph/Hz	380~415V-3Ph-50/60Hz					
Max. circuit/fuse current	A	15.7/20	20.9/25	24.7/32	28.8/40	33.2/40	
Power consumption	Cooling	kW	5.5	7.5	8.9	11.3	13.5
	Heating	kW	6	8.1	10.2	11.7	13.8
Maximum drive IDU NO.	unit	13	16	19	23	26	
Refrigerant Charge volume	kg	6.2	7.1	8.6	10.2	10.5	
Sound pressure level	dB(A)	60	61	63	63	63	
Connecting pipe	Liquid	mm	Φ9.52		Φ12.7		
	Gas	mm	Φ19.05	Φ22.2	Φ25.4	Φ28.6	
	Oil balance	mm	Φ19.05		Φ22.2		
Dimension (W*D*H)	Outline	mm	930*765*1605		1340*765*1605		
	Package	mm	1010*840*1775		1420*840*1775		
Net weight/Gross weight	kg	225/235	225/235	285/300	360/375	360/375	
Loading quantity	40' GP	set	24	24	16	16	16
	40' HQ	set	24	24	16	16	16

50 Hz

Model		NCHS1B	NCHS4B	NCHS8B	
Max. IDU Branches	unit	1	4	8	
No. of connectable IDU of each branch	unit	8	8	8	
Total Connectable IDU	unit	8	32	64	
Max. Capacity of each branch	kW/kW	14	14	14	
Max. Capacity of connectable IDU	kW/kW	14	45	65	
Power supply	V/Ph/Hz	220-240V-1Ph-50Hz			
Power consumption	W	20	30	30	
Maximum drive IDU NO.	unit	1	4	8	
Outdoor Unit Piping Connection	Liquid	mm	Φ9.52	Φ12.7	Φ15.9
	Suction	mm	Φ15.9	Φ22.2	Φ22.2
Indoor Unit Piping Connection	Gas	mm	Φ19.05	Φ28.6	Φ28.6
	Liquid	mm	Φ9.5	Φ9.5	Φ9.5
Indoor Unit Piping Connection	Gas	mm	Φ15.9	Φ15.9	Φ15.9

Key Features of Indoor Units

High Static Pressure Duct Type Indoor Unit



- High static pressure design**
 Static pressure can be up to 150Pa, especially suitable for places in need of long distance airflow.
- Convenient installation**
 You can choose circular air duct or rectangular air duct according to actual needs. Or you can choose different ways of air return.
- Easy maintenance**
 The system has maintenance port for easy maintenance.
- Protection function**
 Anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection, auxiliary electric heating overheat protection.

Low Static Pressure Duct Type Indoor Unit



- **Low static pressure, low noise**

Especially suitable for rooms of compact structure or small installation space. Also, it provides you with a comfortable and quiet living environment.

- **Safety design**

With ceramic PTC electric heating, it features safe operation, high heat exchange efficiency, quick temperature rising, no oxygen consumption, constant temperature, etc.

- **Intelligent drainage device**

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

Note: Please specify if you need this function.

- **Convenient installation**

Tab type plastic filter, detachable fan motor, independent water pump assembly and electric box assembly, all for convenient maintenance.

- **Protection function**

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection.

Slim Ducted Type Indoor Unit



- **Highly Efficient & Energy-saving**

High-efficiency DC brushless motor is used. Its efficiency is improved by over 30% compared with common motor. Evaporator flow path adopts simulating optimized design via the refrigeration system simulation software, which has greatly increased the heat exchange capacity of evaporator.

- **Slim & Small**

The unit is only 200mm's thick and 450mm's deep. Suspended ceiling doesn't have to be very high. It is suitable for ordinary rooms.

- **Wiring of Electric Control Box**

Mounting board of electric control box elements are arranged at both sides of the mounting board of fan motor. There is a wire-cross notch on each side so that wiring at both sides of the mounting board of fan motor is convenient and efficient. Strong and weak current are also separated to ensure the effectiveness of weak current signal transmission.

- **Protection Functions**

Anti-freezing protection, fan motor built-in overload protection, temperature sensor error protection

- **Ultra-quiet**

High-efficiency centrifugal fan and ultralow noise volute are developed with ANSYS and Fluent. They have also gained national patents. Meanwhile, inlet mute valve is adopted so that noise of the complete unit is greatly reduced.

- **Fast & Strong**

Intelligent temperature control technology is adopted. Cooling/ Heating function is fast and strong so that room temperature can quickly reach set temperature.

- **Flexible Installation**

Based on the requirements of building and utilization, different ways of air return and different air supply static pressure can be selected.


- **CAN Bus Communication Technology**

System response speed is faster and communication is more reliable. Auto addressing, non-polar communication, free wire matching

- **Convenient Operation & Maintenance**

Electric control box is attached independently so that it can be detached as a whole, which is convenient for maintenance. The installation and maintenance of fan and motor is also convenient.

4-way Cassette Indoor Unit



- **Strong and balanced airflow**

Unit features auto operation, 4-way airflow, 7 fan speeds and strong circulating airflow.

- **Ultra-low noise operation**

DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.

- **Intelligent drainage device**

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

- **DC inverter motor**

With good speed regulation performance, motor efficiency improved by 30% v.s. normal motor.

- **Protection function**

Water overflow protection, anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection, auxiliary electric heating overheat protection (This function is not included in pure heat pump unit).

Compact 4-way Cassette Indoor Unit



- **Compact Design for Easy Installation**

Units maintain the uniform length and width with consistent ceiling opening and panel dimension, convenient for design and installation;


- **Ultra-low noise operation**

DC inverter motor can realize stepless speed regulation to lower noise. Indoor unit can be set to work under auto quiet mode via wired controller.

- **Intelligent drainage device**

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

2-way Cassette Indoor Unit



- **Beautiful Appearance**

With beautiful and elegant front panel, it is congenial to the indoor surroundings.

- **Intelligent drainage device**

Water height difference up to 1.0m, which can effectively drain out condensing water and save space.

- **Two-way air flow design**

Two-way air outlet, to stretch air outlet distance and solve air supply problem of elongated room

- **Multiple protections**

Anti-freezing protection, temperature malfunction protection, fan motor overload protection, auxiliary electric heating overheat protection and humidity sensor protection.

1-way Cassette Indoor Unit



- **Small installation space**

With 185mm ultrathin design, unit can be installed in the ceiling of 19cm deep.

- **Detachable grille and long life filter**

Grille is detachable for easy cleaning. With long life filter, cleaning cycle is 20 times longer.

- **High drain pump lift**

Drain pump lift reaches 1.0m, which can effectively drain out water.

- **Protection function**

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection, auxiliary electric heating overheat protection(This function is not included in pure heat pump unit).

Wall-mounted Indoor Unit



- **Comfortable and balanced airflow, up&down air outlet**

Up air outlet: In cooling, cool air blows out horizontally and then gradually drops.

Down air swing: In heating, warm air blows downward and then gradually climbs up.

- **Triple defenders for better purification**

Mildew-proof filter, electrostatic fibre and anti-biotic fibre adopted to remove dust, smell, bacteria and mildew.

- **Cold air prevention design**

During heating in winter, cold air prevention function is enabled so that air won't be blown out until it's warm.

- **Multiple protections**

Anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection, auxiliary electric heating overheat protection(This function is not included in pure heat pump unit).

Floor Ceiling Type Indoor Unit



- **Hoisted or seated, flexible installation**

Unit can be hoisted or seated. When seated, suspended ceiling is not needed.

- **Beautiful appearance**

With beautiful and elegant front panel, it is congenial to the indoor surroundings.

- **Protection function**

Anti-freezing protection, temperature sensor malfunction protection, fan motor overload protection.

- **Horizontal and vertical air swing**

Wider air swing range for your comfortable working and living environment.

Console Indoor Unit



- **Multiple fan speed**

The fan can operate in multiple speed and satisfy different air flow volume requirements.

- **Detachable grille and long life filter**

Grille is detachable for easy cleaning. With long life filter, cleaning cycle is 20 times longer.

- **High drain pump lift**

Drain pump lift reaches 1.0m, which can effectively drain out water.

- **Protection function**

Water overflow protection, anti-freezing protection, fan motor overload protection, temperature sensor malfunction protection, auxiliary electric heating overheat protection(This function is not included in pure heat pump unit).

Floor Standing Indoor Unit



- **Wide Application**

It can be widely adopted in hotels, restaurants, office, etc.

- **Auto clean to ensure a healthy life**

After turning off the unit, the indoor fan will keep running in low speed for a moment to dry the inner components and parts, in order to prevent mildew and keep user healthy.


Fresh Air Processing Indoor Unit

Airflow volume: 1200~6000m³/h
 Applicable range: Residential houses, villas, business buildings, hotels, apartments, etc.



One system, two functions

- Adopted with DC inverter technology, Fresh Air DC Inverter Multi VRF System features air conditioning function and fresh air function.




Enjoy fresh air

- Airflow volume: 1200~4000m³/h, cooling capacity: 14-45kW
 Applicable for all kinds of structure.
- Direct evaporative cooling adopted, air conditioning+fresh air can be realized accurately and precisely.
- DC inverter technology adopted, constant humidity is enabled with less power consumption.
- Integrated system control with Gree GMV Multi VRF System.




Air conditioning and fresh air, two in one

- Less investment**
 Fresh Air DC Inverter Multi VRF System can be combined with Gree GMV5. For a same room, if the same amount of fresh air is to be taken, then the cost of GMV5+Fresh air unit is equivalent to the cost of GMV+Air exchange fan.
- Less operation cost**
 Unit can control refrigerant output according to actual needs to ensure constant airflow temperature. By adjusting power output, light-load but high power operation can be avoided. Thus, operation cost can be greatly reduced.
- Less installation space**
 Save installation space for outdoor units. Especially suitable for places that have restricted installation space.



1.13 Air Handler

- Highly Flexible Installation**
 The unit is designed for outdoor installation and less indoor space taking, allowing easy installation and maintenance. The unit can be installed on the ground or on the roof of the building, which means the installation is totally flexible depending on the project requirement.
- Cold Air Prevention Design**
 When heating in winter, cold air prevention function is enabled so that air won't be blown out until it's warm.
- Long life and Washable Filter**
 The filter is easy to be dismantled and installed. You can use dust collector or water to clear away the dust.



Indoor Units Lineup

Specifications of Indoor Units

Type of indoor unit	Specification	22	25	28	32	36	40	45	50	56	63	71	72	80	90	100	112	125	140	160	224	280	450
High Static Pressure Duct Type Unit										●	●	●		●	●	●	●	●	●	●	●	●	●
Low Static Pressure Duct Type Unit		●	●	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●				
Slim Ducted Type Indoor Unit		●	●	●	●	●	●	●	●	●	●		●										
4-way Cassette Unit				●		●		●	●	●	●	●		●	●	●	●	●	●	●	●		
Compact 4-way Cassette Indoor Unit		●		●		●		●	●	●													
2-way Cassette Indoor Unit				●		●		●	●	●	●	●											
1-way Cassette Unit		●		●		●		●	●														
Wall-mounted Type Unit		●		●		●		●	●	●	●	●											
Floor Ceiling Type Indoor Unit				●		●		●	●	●	●			●		●	●	●	●				
Console Indoor Unit		●		●		●		●	●														
Floor Standing Type Indoor Unit													●			●							
Fresh Air Processing Indoor Unit																			●	●	●	●	●
Air handler													●	●	●	●	●	●	●	●			

High Static Pressure Duct Type Indoor Unit 50/60 Hz

Model		GMV-ND56PHS/A-T	GMV-ND63PHS/A-T	GMV-ND71PHS/A-T	GMV-ND80PHS/A-T	GMV-ND90PHS/A-T	
Capacity	Cooling	kW	5.6	6.3	7.1	8.0	9.0
	Heating	kW	6.3	7.1	8.0	9.0	10.0
Power supply	V/Ph/Hz						220~240/1/50 & 208~230/1/60
Power consumption	W	120	120	130	130	200	
Airflow volume(H/M/L)	m ³ /h	1000/800/600	1000/800/600	1100/900/700	1100/900/700	1700/1450/1100	
	CFM	590/471/355	590/471/355	650/530/410	650/530/410	1000/853/650	
Rated Current ²	Cooling	A	0.6	0.6	0.6	0.6	1.0
	Heating	A	0.6	0.6	0.6	0.6	1.0
	Water Heating	A	/	/	/	/	/
ESP	Pa	70/0~100					
Sound pressure level(H/M/L)	dB(A)	44/40/36	44/40/36	45/41/37	45/41/37	46/44/42	
Connecting pipe diameter	Liquid	mm	φ9.52	φ9.52	φ9.52	φ9.52	φ9.52
	Gas	mm	φ15.9	φ15.9	φ15.9	φ15.9	φ15.9
Drain pipe	External dia.	mm	φ25	φ25	φ25	φ25	φ25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimension (WxDxH)	Outline	mm	1271x558x268			1229x775x290	
	Package	mm	1348x597x283			1338x877x305	
Net weight/Gross weight	kg	35/40	35/40	35/40	35/40	47/54	
Loading	40' GP	set	192	192	192	192	128
	40' HQ	set	216	216	216	216	128

Model		GMV-ND100PHS/A-T	GMV-ND112PHS/A-T	GMV-ND125PHS/A-T	GMV-ND140PHS/A-T	GMV-ND160PHS/A-T	GMV-ND224PHS/A-T	GMV-ND280PH/A-T			
Capacity	Cooling	kW	10.0	11.2	12.5	14.0	16.00	22.4	28.0		
	Heating	kW	11.2	12.5	14.0	16.0	18.00	25.0	31.0		
Power supply	V/Ph/Hz								220~240/1/50 & 208~230/1/60		
Power consumption	W	200	200	220	220	560	800	900			
Airflow volume(H/M/L)	m ³ /h	1700/1450/1100	1700/1450/1100	2000/1550/1200	2000/1700/1200	3100	4000	4400			
	CFM	1000/853/650	1000/853/650	1175/912/706	1175/912/706	1824	2355	2590			
Rated Current ²	Cooling	A	1.0	1.0	1.0	1.0	4	4.1	4.6		
	Heating	A	1.0	1.0	1.0	1.0	4	4.1	4.6		
	Water Heating	A	/	/	/	/	/	/	/		
ESP	Pa	70/0~100						50	150/50~200	150/50~200	
Sound pressure level(H/M/L)	dB(A)	46/44/42	46/44/42	48/45/42	48/46/44	55.0	54.0	55.0			
Connecting pipe diameter	Liquid	mm	φ9.52	φ9.52	φ9.52	φ9.52	φ9.52	φ9.52			
	Gas	mm	φ15.9	φ15.9	φ15.9	φ15.9	φ19	φ22.2			
Drain pipe	External dia.	mm	φ25	φ25	φ25	φ25	φ30	φ30			
	Thickness	mm	2.5	2.5	2.5	2.5	1.5	1.5			
Dimension (WxDxH)	Outline	mm	1229x775x290			1497x799x389		1483x791x385		1686x870x450	
	Package	mm	1338x877x305			1578x883x400		1758x883x470		1788x988x580	
Net weight/Gross weight	kg	47/54	47/54	47/54	47/54	79/103	82/104	105/140			
Loading	40' GP	set	128	128	128	128	75	65	52		
	40' HQ	set	128	128	128	128	75	65	52		

Low Static Pressure Duct Type Indoor Unit 50/60 Hz

Model		GMV-ND22PLS/A-T	GMV-ND25PLS/A-T	GMV-ND33PLS/A-T	GMV-ND36PLS/A-T	GMV-ND36PLS/A-T	
Capacity	Cooling	kW	2.2	2.5	2.8	3.2	3.6
	Heating	kW	2.5	2.8	3.6	3.6	4.0
Power supply	V/Ph/Hz						220~240/1/50 & 208~230/1/60
Power consumption	W	35	35	35	43	43	
Airflow volume(H/M/L)	m ³ /h	450/350/250	450/350/250	450/350/250	550/450/350	550/450/350	
	CFM	265/206/147	265/206/147	265/206/147	325/265/206	325/265/206	
Rated Current ²	Cooling	A	0.2	0.2	0.2	0.2	0.2
	Heating	A	0.2	0.2	0.2	0.2	0.2
	Water Heating	A	/	/	/	/	/
ESP	Pa	15/0~30					
Sound pressure level(H/M/L)	dB(A)	31/28/25	31/28/25	31/28/25	32/30/27	32/30/27	
Connecting pipe diameter	Liquid	mm	φ6.35	φ6.35	φ6.35	φ6.35	φ6.35
	Gas	mm	φ9.52	φ9.52	φ9.52	φ12.7	φ12.7
Drain pipe	External dia.	mm	25	25	25	25	25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimension (WxDxH)	Outline	mm	700 x 615 x 200				
	Package	mm	893x743x305				
Net weight/Gross weight	kg	22/27	22/27	22/27	22/28	22/28	
Loading	40' GP	set	192	192	192	192	192
	40' HQ	set	192	192	192	192	192

Console Indoor Unit 50/60 Hz

Model			GMV-ND22C/A-T	GMV-ND28C/A-T	GMV-ND36C/A-T	GMV-ND45C/A-T	GMV-ND50C/A-T
Capacity	Cooling	kW	2.2	2.8	3.6	4.5	5.0
	Heating	kW	2.5	3.2	4.0	5.0	5.5
Power supply	V/Ph/Hz		220-240/1/50 & 208-230/1/60				
Power consumption	W		60	60	60	60	60
Airflow volume(H/M/L)	m³/h		500-430/370/280	500-430/370/280	600-520/440/360	650-620/500/410	650-620/500/410
	CFM		294-253/217/164	294-253/217/164	353-306/259/212	383-365/294/241	383-365/294/241
Rated Current ²	Cooling	A	0.15	0.15	0.15	0.15	0.15
	Heating	A	0.15	0.15	0.15	0.15	0.15
	Water Heating	A	/	/	/	/	/
ESP	Pa		0	0	0	0	0
Sound pressure level(H/M/L)	dB(A)		38/33/26	38/33/26	40/37/32	46/41/35	46/41/35
Connecting pipe diameter	Liquid	mm	6.35	6.35	6.35	6.35	6.35
	Gas	mm	9.52	9.52	9.52	12.7	12.7
Drainpipe	External dia.	mm	17.2	17.2	17.2	17.2	17.2
	Thickness	mm	1	1	1	1	1
Dimension (WxDxH)	Outline	mm	700/215/600	700/215/600	700/215/600	700/215/600	700/215/600
	Package	mm	788/283/697	788/283/697	788/283/697	788/283/697	788/283/697
Net weight/Gross weight	kg		16/19	16/19	16/19	16/19	16/19
Loading	40' GP	set	387	387	387	387	387
	40' HQ	set	433	433	433	433	433

Air Handler 60 Hz

Model			GMV-ND71A/A-T	GMV-ND90A/A-T	GMV-ND100A/A-T	GMV-ND112A/A-T	GMV-ND140A/A-T	GMV-ND160A/A-T
Capacity	Cooling	-	7.03	8.79	10.26	12.02	13.48	17
	Heating	kW	6.74	8.79	9.96	11.58	13.19	16.12
Power supply	kW		208-230/1/60					
Power consumption	V/Ph/Hz		140	170	245	245	368	368
Airflow volume(H/M/L)	W		1400	1660	1940	2210	2380	2800
	m³/h		825	980	1140	1300	1400	1650
Rated Current ²	Cooling	A	1.52	1.35	2.00	2.00	2.50	4.60
	Heating	A	1.52	1.35	2.00	2.00	2.50	4.60
	Water Heating	A	/	/	/	/	/	/
ESP	Pa		25	37	37	37	50	50
Sound pressure level(H/M/L)	dB(A)		48	50	48	50	50	55
Connecting pipe diameter	Liquid	mm	φ9.52	φ9.52	φ9.52	φ9.52	φ9.52	φ12.7
	Gas	mm	φ15.9	φ19	φ19	φ22.2	φ22.2	φ28.5
Drainage Connection Size (Outer Diameter×Wall Thickness)	mm		φ19	φ19	φ19	φ19	φ19	φ19
Dimension (WxDxH)	Outline	mm	460*540*1105	460*540*1105	540*540*1224	540*540*1224	630*540*1224	630*540*1224
	Package	mm	514*617*1155	514*617*1155	594*617*1274	594*617*1274	684*618*1280	684*618*1280
Net weight/Gross weight	kg		53/57	55.5/59	65/70	67/72	79/84	80/86
Loading	40' GP	set	164	164	85	85	85	85
	40' HQ	set	172	172	114	114	114	114

Fresh Air Processing Indoor Unit 50 Hz

Model			GMV-NX140P/A(X1.2)-K *	GMV-NX224P/A(X2.0)-M *	GMV-NX280P/A(X2.5)-M *	GMV-NX280P/A(X3.0)-M *	GMV-NX450P/A(X4.0)-M *
Capacity	Cooling	kW	14.0	22.4	28.0	28.0	5.0
	Heating	kW	10.0	16.0	20.0	20.0	5.5
Power supply	V/Ph/Hz		220-240/1/50	380-415/3/50			
Power consumption	W		360	740	760	1060	1240
Airflow volume(H/M/L)	m³/h		1200	2000	2500	3000	4000
	CFM		705	1175	1470	1765	2355
Rated Current ²	Cooling	A	1.82	1.32	1.36	1.89	2.22
	Heating	A	1.82	1.32	1.36	1.89	2.22
	Water Heating	A	/	/	/	/	/
ESP	Pa		150		200		
Sound pressure level(H/M/L)	dB(A)		42	47	48	51	52
Connecting pipe diameter	Liquid	mm	φ9.52	φ9.52	φ9.52	φ9.52	φ12.7
	Gas	mm	φ15.9	φ19.05	φ22.2	φ22.2	φ28.6
Drainpipe	External dia.	mm	25	25	25	25	25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Dimension (WxDxH)	Outline	mm	1463 x 756 x 300	1500 x 1000 x 500			1700 x 1100 x 650
	Package	mm	1514x785x360	1840x1200x673			1890x1460x835
Net weight/Gross weight	kg		63.5/71	130/182	134/188	134/188	208/266
Loading	40' GP	set	84.0	18.0	18.0	18.0	16.0
	40' HQ	set	98.0	18.0	18.0	18.0	16.0

Note: * This series can be matched with GMV5(Top discharge outdoor unit)only.

Floor Standing Type 50/60 Hz

Model			GMV-ND100L/A-T	GMV-ND140L/A-T
Capacity	Cooling	kW	10	14
	Heating	kW	11	15
Power supply	V/Ph/Hz		220-240/1/50 & 208-230/1/60	
Power consumption	W		180	180
Airflow volume(H/M/L)	m³/h		1600/1500/1300	1700/1600/1400
	CFM		942/883/765	1000/942/824
Rated Current ²	Cooling	A	1.5	1.5
	Heating	A	1.5	1.5
	Water Heating	A	/	/
ESP	Pa		0	0
Sound pressure level(H/M/L)	dB(A)		51/50/48	52/50/48
Connecting pipe diameter	Liquid	mm	9	9
	Gas	mm	16	16
Drainpipe	External dia.	mm	31	31
	Thickness	mm	4.5	4.5
Dimension (WxDxH)	mm		1870x580x400	1870x580x400
Net weight/Gross weight	kg		53/73	57/77
Loading	40' GP	set	67	67
	40' HQ	set	67	67

Control System




Smart Model Selection Software and Debugging Software

Model Selection Software

Gree multi VRF selection software is a kind of advanced computer program for selecting models automatically in sales and project bidding. It integrates multi VRF selection logic and computer software to provide a user-friendly interactive interface, which is able to automatically recommend suitable models to user according to ambient condition of project and user's demand. It is applicable for GMV5.


Flexible Setting of Project Design Conditions

When setting up a new model selection project, the information of customer, designer, unit series and working conditions, etc. can be set as relevant parameters of model selection, and then sent to data report for checking during project design.




Accurate Recommendation of Indoor Unit and Outdoor Unit

When selecting indoor unit model with the software, you can use automatic recommendation way only by inputting the required air conditioning load and indoor unit series. Then the software will recommend the suitable indoor unit model automatically according to model selection logic. When selecting outdoor unit model, you can use automatic recommendation way directly to select the suitable outdoor unit model.




Free Modification of Selected Models

If you are not satisfied with the system recommended by the software, you can select or adjust indoor unit model through alternate selection function.




Edit IDU




Confirmation

One-click Modification and System Validation

When reselection is needed due to major changes of indoor units, one-click recommendation function can be adopted to reselect all indoor units with simple operation; after finishing model selection, you can use one-click system validation function to check various parameters requirements of air conditioning system.




One-click Recommendation




System Validation

Optional Controller Configuration and Electric System Configuration

The software will offer controller model matched with the system. The user only needs to choose controller type and then the software will output the controller model into the report.




Optional Controller Configuration




Electric System Configuration

Save Model Selection Project, Output Data Report and System Wiring Diagram

After finishing system selection and various system configurations, the user can save model selection project freely for future reference. Then the user can output relevant parameters of selected project in an excel form and output system wiring CAD diagram for reference in installation.




Save Data



Units Setting

Part 3 System			
3.1 Unit Output			
Indoor Unit Capacity Status			
Total capacity of R101	Total capacity of R01	Indoor Unit Capacity Status	
100000	100000		
Indoor Unit	Capacity (kW)	Capacity (kW)	Capacity (kW)
GMV-200R001	20000	20000	20000
GMV-200R002	20000	20000	20000
GMV-200R003	20000	20000	20000
GMV-200R004	20000	20000	20000
GMV-200R005	20000	20000	20000

Parameters Output in Excel Form




Output CAD Wiring Diagram

Intelligent Debugging Software

GMV5 offers an intelligent debugging software to the end-users for faster construction needs.


Monitoring Functions

- Fully control the operation status of each device of the system;
- Hover the mouse over the parameter to display its remarks.
- The online devices will be displayed in a tree structure;
- Display the information of air conditioner in divided regions;
- Each display region can be moved or concealed;
- Display updated status of units in real time;



Control Functions

- Control the operation of unit as you like;
- Comprehensive control of outdoor unit, indoor unit, water tank, hydro box, etc.;
- Real-time display of current status or status after being controlled;
- Both single control and group control are available.




Project Debugging Functions

- One-click and automatic project debugging;
- Project debugging is arranged step by step from left to right;
- Manual intervention and skipping of some debugging phases are available.
- Green icons will be displayed for the items finishing debugging; red icons will be displayed for the items having debug exception; light yellow icons display debugging information;




Auto Data-Saving Function

Data will be saved automatically. Database saving path can be changed or data document can be generated repeatedly.




USB Data Converter

Users can use USB data converter to freely convert CAN/HBS/RS485 data into USB data, achieving data interchange between computer and air conditioner.




Auto Direction of Connection Way

The wiring diagram will direct connection way automatically, so that the user can get the connection way quickly.



Multiple Intelligent Remote Control Management

Gree GMV5 provides multiple intelligent controls in order to satisfy all demands. It can control both a room and a building at the same time.




Visualized Management

- System has a map that can display air conditioners' locations in rooms and buildings.
- System is able to measure the status and number of air conditioners in different levels



Everyday Management

- **Setting for daily operation**
 - Management in days/weeks/months/years
 - Management in each unit
 - Simple display for management
- **Other functions**
 - Power on/off, modes, humidity, fan speed
 - Waste of energy that may be caused by forgetting to turn off the air conditioner can be avoided
- **Everyday Management at different locations**
 - Management for overtime working
 - Management for meal breaks
 - Management for working time



Group Management

- **Central management in groups**
 - Free choices of dividing groups
 - Central control over power on/off
 - Central control over temperature
 - Central control over modes
 - Central control over user authority




Authority Management

- **Only for indoor units**
 - Limited control over power on/off
 - Limited control over temperature
 - Limited control over modes



Statistics Analysis

- **Recording statistics**
System can self generate graphs of statistics for easy management and analysis.
- **Recording errors**
System can show the information of errors in charts and send alarms of errors through emails.
- **Recording operation**
System can record users' daily operation.



Calculating Cost of Electricity

- Auto calculation according to users
- According to the operating time, modes, flow of refrigerant, humidity and other factors, system can calculate the cost of electricity for users in different locations.
 - Detailed information of bills and operation can be provided.



Energy Management

- **Analysis of energy cost**
 - Air conditioners that cost much energy
 - Air conditioners that are set in low temperature
 - Air conditioners with bad cooling performance
- **Ways to save energy based on the following aspects:**
 - Operating time
 - Unit is on too early
 - Unit is off too late
 - Comfort
 - Cost of electricity/cost of electricity per square meter

Energy saving

- **Limits on electricity**
 - Analysis on the cost of electricity
 - Set the maximum cost of electricity and unit will be operating in limited conditions when the maximum number is reached.
 - System can remind users the cost of electricity during operation and give suggestions on energy saving.
- **Economic operation**
System is able to operate under an energy-saving condition



VIP Management

System can provide independent and unique service to VIP users.



Wired Controller and Remote Controller

There are two kinds of controllers: wired controller and remote controller. The system provides various controls for users, such as cooling, heating, dehumidifying and fan etc., users can select it flexibly according to their own using methods.

Wired controller XK46



- LCD with black background and white words; touch buttons;
- Clock can be displayed and set; 24 hours timer setting for on/off;
- 7 levels of fan speed, up & down swing and left&right swing;
- Can be switched in auto, cooling, dehumidifying, fan, heating, floor heating, 3D heating and space heating operation modes;
- Master and slave wired controllers can be set; simultaneous control over several IDUs is available;
- Available functions: sleep, ventilation, quiet/auto quiet, light, energy saving, auxiliary heating, drying, memory, low-temperature dehumidifying, absence in heating, controllable auxiliary heating in dehumidifying, filter cleaning reminder, etc.;
- Detect ambient temperature; receive infrared remote controller signal;
- With project parameters viewing and setting functions.

Wired controller XK49 (For hotel)



- With simplified functions, mechanical buttons, back lighting LCD and convenient operation;
- Can be switched in auto, cooling, dehumidifying, fan and heating operation modes;
- Master and slave wired controllers can be set; simultaneous control over several IDUs is available;
- Detect ambient temperature; receive infrared remote controller signal;
- With system parameters viewing and setting functions;
- 7 levels of fan speed, up&down swing;
- Door control system can be connected.

Wired controller XK62



- Small and fashionable outlook with thickness only of 11 mm; LCD with black background and white words; touch buttons;
- Clock can be displayed and set; 24 hours timer setting for on/off;
- 7 levels of fan speed, up&down swing and left&right swing;
- Can be switched in auto, cooling, dehumidifying, fan, heating, floor heating, 3D heating and space heating operation modes;
- Master and slave wired controllers can be set; simultaneous control over several IDUs is available;
- Available functions: sleep, ventilation, quiet/auto quiet, light, energy saving, auxiliary heating, drying, memory, low-temperature dehumidifying, absence in heating, controllable auxiliary heating in dehumidifying, filter cleaning reminder, etc.;
- Detect ambient temperature; receive infrared remote controller signal;
- With project parameters viewing and setting functions.

Wired controller XK55



- Elegant appearance;
- High-resolution color LCD;
- Capacitive touch control; receive infrared remote controller signal;
- Various timing functions: three weekly timers and one countdown timer can be set simultaneously; mode, temperature and fan speed can be preset in weekly timer;
- Complete system functions; each function will be implemented in an individual page with interactive and humanized interface;
- Various personalized functions, e.g. setting brightness and backlight time;
- Sufficient viewing functions, e.g. viewing on/off status and after-sales service hot line.

Remote controller YAP1F




- Can be switched in auto, cooling, dehumidifying, fan and heating operation modes;
- Besides turbo, 6 levels of fan speed can be set;
- Available functions: child lock, drying, health, ventilation, turbo, sleep, light, absence, i-feel and timer;
- Clock display and indoor/outdoor ambient temperature viewing functions;
- Up & down swing and left & right swing.




- **Single control of one unit**

Each indoor unit has an independent controller.



- **Multiple control of one unit**

One indoor unit can be controlled by several wired controllers at different places.




Remote Controller YV1L1



- Back lighting LCD;
- Can be switched in auto, cooling, dehumidifying, fan, heating, floor heating, 3D heating and space heating operation modes;
- 7 levels of fan speed, up&down swing and left&right swing;
- Available functions: child lock, energy saving, drying, health, ventilation, quiet/auto quiet, sleep, light, absence, low-temperature dehumidifying, i-feel and timer;
- With clock display, system parameters viewing and setting functions.


- **Central control of several indoor units**

One wired controller can control as many as 16 indoor units.



- **Joint control of remote controller and wired controller**

Users can control one unit with two types of controllers: a remote controller which is convenient and flexible; or a wired controller which includes every function of an air conditioner.



Smart Zone Controller and Central Controller

Smart zone controller CE53-24/F(C)



- 1280*800 high-resolution color LCD;
- 7" capacitive touch screen for easy operation;
- Shielding function of single unit, group and all IDUs (shielding on/off, mode, temp setting, etc.);

- With various functions: centralized control(control all indoor units), group management(support DIY grouping), schedule management(setting of several schedules) and single unit control(on/off, mode, temp setting, fan speed, quiet, swing control, etc.);
- Provide naming of indoor units, selection of icons and personalized settings(setting background, backlight, etc);
- Up to 32 units can be centrally controlled;
- Elegant and fashionable appearance;
- Embedded installation in wall with projecting thickness only of 11mm;
- Connectable with network of indoor units or outdoor units;
- Independent power supply in 110~240V wide voltage range;
- With project setting, parameter viewing, malfunction record and access management functions.

Central controller CE52-24/F(C)



- 1280*800 high-resolution color LCD;
- 7" capacitive touch screen for easy operation;
- With project setting, parameter viewing, malfunction record and access management functions.


- With various functions: centralized control(control all indoor units), group management(support DIY grouping), schedule management(setting of several schedules) and single unit control(on/off, mode, temp setting, fan speed, quiet, swing control, etc.);
- Shielding function of single unit, group and all IDUs (shielding on/off, mode, temp setting, etc.);
- Provide naming of indoor units, selection of icons and personalized settings(setting background, backlight, etc);
- Up to 128 units can be centrally controlled;
- Elegant and fashionable appearance;
- Embedded installation in wall with projecting thickness only of 11mm;
- Connectable with network of indoor units or outdoor units;
- Independent power supply in 110~240V wide voltage range;

BACnet Gateway

BACnet gateway kits MG30-24/D2(B) are intended to realize the data exchange between the air conditioning unit and BAS, and providing the standard BACnet/IP building interface and 8 I/O interfaces, one of which is the fire alarm signal interface. The status of the other 7 I/O interfaces is mapped to the specific objects of the BACnet/IP bus and can be defined by the user.



Applicable models: GMV5 All DC Inverter Multi VRF System, GMV5 DC Inverter Multi VRF System, GMV DC Inverter Water Cooled Heat Pump Multi VRF System.




- International standard BACnet/IP interface, which has passed BTL certification;
- Real-time monitoring of unit operation status, e.g. on/off, mode, temperature;
- Real-time response to the control of unit (on/off, mode setting and speed setting, etc.) by monitoring software;
- Monitor unit errors;

- Lock unit operation statuses, directing at all control functions of unit itself or a certain setting function;
- Achieve cooling and heating temperature limitation functions;
- 8 DI/DO interfaces for receiving fire alarm signal and user's definition logic;
- Big storage capacity of unit operation data for 6 months.

Modbus Gateway

Modbus Gateway provides GMV5 system with the Modbus protocol interface when connecting to the Building Management System(BMS) in order to achieve central control and remote control over GMV5 system by BMS.



Applicable models: GMV5 All DC Inverter Multi VRF System, GMV5 DC Inverter Multi VRF System, GMV DC Inverter Water Cooled Heat Pump Multi VRF System.

- Real-time monitoring of unit operation status, e.g. on/off, mode, temperature;
- Real-time response to the control of unit (on/off, mode setting and speed setting, etc.) by monitoring software;
- Control all the units switches of on and off.
- Monitor unit errors;
- One Modbus bus can support up to 255 gateways. One Modbus gateway can support at most 16 outdoor units(up to 64 modular outdoor units) and 128 indoor units;
- Lock unit operation statuses, directing at all control functions of unit itself or a certain setting function;
- Linkage control, supporting 5 DI and 5 DO for receiving fire alarm signal and user's definition logic;
- CAN, RS485 communication ports are non-polar, convenient for construction wiring;
- Achieve cooling and heating temperature limitation functions;
- 110~240VAC wide voltage range, adapted to the power supply of each country and region.

Control System Lineup

Controlling system	Product series	Cassette Type	(High ESP, Low ESP, Slim Ducted) Duct Type	Fresh Air Processing	Wall mounted Type	Floor Ceiling Type	Console Type	Floor Standing Type	Air Handler
Wireless Controller	YAP1F		●	○	○	●	●	●	○
	YV1L1		○	○	○	○	○	○	○
Wired controller	XK46		○	●	●	○	○	○	●
	XK49		○	○	○	○	○	○	○
	XK62		○	○	○	○	○	○	○
	XK55		○	○	○	○	○	○	○
	JS05(receiver)		○	○	○				
Centralized Controller	CE52-24/F(C)		○	○	○	○	○	○	○
Smart Zone Controller	CE53-24/F(C)		○	○	○	○	○	○	○
Long-distance monitoring software	FE31-00/AD(BM)		○	○	○	○	○	○	○
BMS Accessories	Communication module(modbus)	ME30-24/E4(M)		○	○	○	○	○	○
	GMV BACnet gateway (BACnet)	MG30-24/D2(B)		○	○	○	○	○	○
Other modules	Optoelectronic isolated converter	RS232-RS422/485		○	○	○	○	○	○
	Optoelectronic isolated signal multiplier	RS-422/485		○	○	○	○	○	○

Note: ● means standard, ○ means optional.


Energy Recovery Ventilation(ERV)



- Air flow: 350~3000m³/h
- Energy Recovery Ventilation System can introduce the fresh air freely on the condition that all the windows closed or exhausted fan uninstalled. It can solve the problem of stagnant air effectively.
It is usually installed in the ceiling of corridor and supplies fresh air to each room through ducts.

Adopt Advanced Heat Exchange Core

ERV adopts cross flow plate exchanger with air volume below 3000m³/h. Fresh air will be introduced and internal leakage is low, which effectively prevent pollution to fresh air.




Double-way Ventilation for Fresh Air

ERV can not only introduce lots of fresh air, but also discharge the stagnant air at the same time, which effectively minimizes the toxic air from the inner and other materials. The ventilation effect is very obvious, ensuring enough supply of fresh air to the indoor space.

No Cross Contamination for Ensuring Healthy Fresh Air

The unique cross-flow heat exchange valve sub-assy is adopted. There is only energy exchange between indoor air and outdoor air with little exchange of air, which effectively prevents cross contamination and "air-condition" disease.



Pretreatment of Fresh Air for Energy-saving

When fresh air is introduced, its temperature and humidity will be exchanged with the discharged warm air. As the fresh air is preheated and humidified, energy is saved and load of unit is reduced.

Energy Recovery Ventilation(ERV)

Model			FHBQ-D3.5-K	FHBQ-D5-K	FHBQ-D8-K	FHBQ-D10-K	FHBQ-D15-M	FHBQ-D20-M	FHBQ-D30-M	FHBQ-D5-D	FHBQ-D8-D*1	FHBQ-D10-D	FHBQ-D15-D*1
Air flow volume	H/M/L	M3/ h	350	500	800	1000	1500	2000	3000	500	800	1000	1500
ESP	H/M/L	Pa	100	100	110	110	150	150	220	100	100	110	150
Temperatur exchange efficiency	H/M/L	%	71.00	68.00	70.00	73.00	73.00	71.00	70.00	68.00	70.00	75.00	73.00
Enthalpy exchange efficiency(HM/L)	Heating	%	65.00	62.00	63.00	66.00	65.00	62.00	62.00	62.00	63.00	66.00	65.00
	Cooling	%	61.00	57.00	60.00	62.00	60.00	58.00	58.00	57.00	60.00	62.00	60.00
Power supply	Ph/V/Hz		1/220/50	1/220/50	1/220/50	1/220/50	3/380/50	3/380/50	3/380/50	1/220/60	1/220/60	1/220/60	3/220/60
Power input	KW		0.165	0.262	0.40	0.44	0.80	0.95	2.80	0.262	0.50	0.50	1.10
Sound Pressure Level	Db(A)		37	39	45	46	48	50	54	39	50	48	60
Dimension (W*D*H)	Outline	mm	800*879*306	800*879*306	832*1016*380	832*1016*380	1210*1215*452	1210*1215*452	1340*1550*572	600*879*306	832*1016*380	832*1016*380	1210*1215*452
	Package	mm	1050*1165*315	1050*1165*315	1087*1320*400	1087*1320*400	1540*1550*470	1540*1550*470	1610*1710*700	1050*1165*315	1087*1320*400	1087*1320*400	1540*1550*470
Net weight	kg		45	45.0	57.0	57.0	110.0	110.0	215.0	45.0	57.0	57.0	110.0
Gross weight	kg		53	53.0	66.5	66.5	130.0	130.0	236.0	53.0	66.5	66.5	130.0
Loading quantity	40'GP	set	147	147	85	59	37	37	24	147	59	59	37
	40'HQ	set	168	168	104	67	44	44	24	168	67	67	44
Standard wired remote controller			Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151	Z5N151

Note:
*1:This product only gets CB certification.

Control System Lineup

Product series			ERV
Control system			
Wired controller	Z5N151		●
Interface of the main board	BMS		●
Optoelectronic isolated converter	RS232-RS422/485		○
Optoelectronic isolated signal multiplier	RS-422/485		○

Note: ● means standard, ○ means optional.

Note

Note

Note
